


# Lumina RF Full Phase 1000W Dimmer

lumina rf



## BASIC OPERATION

Introducing the Lumina™ RF 1000W Dimmer (DL1KD), a line-powered component of the Lumina RF Solutions product line. This device allows dimming of full phase loads as part of the Lumina Gateway and Lumina RF Eco-System. Lumina RF products ensure energy savings in new construction and retrofits and the Lumina Gateway functions as an energy management coordinator, allowing for wireless automated control of loads via remote control from a tablet or smartphone app.

The DL1KD is a robust manual rocker dimmer switch used to provide wireless control of lighting loads including high-inrush LED loads. The DL1KD Wall Dimmer is compatible with 2.4 GHz Lumina RF wireless products. When connected with a Lumina Gateway it allows facilities to create scalable wireless energy management systems.

Connect other Lumina RF devices and add the OmniTouch 7 Touchscreen Interface for seamless centralized control, scheduling and remote access. The DL1KD is the optimal solution for retrofit

applications where LED, incandescent or fluorescent lighting controls are required and additional wiring devices are cost prohibitive.

## APPLICATIONS

- Retrofits
- Conference Rooms
- Lounges
- Restaurants
- Executive offices
- New construction
- Transceiver: 2-way communication with acknowledgement

## FEATURES

- **Use with Lumina RF Eco-System**
- **Aesthetically pleasing intuitive design** – rocker switch and slender raise/lower side bar for ON/OFF, raise/lower control
- **Wireless mesh network** – self-healing mesh network feature has no hardwired backbone and connects all products together for a more robust and reliable system without wires
- **Code compliant energy management functionality** – meets energy code requirements for ASHRAE 90.1 and California Title 24
- **LED flexibility** – enable, disable or turn OFF LED lights after five seconds for applications where brightness is a factor (i.e. hospitality)
- **LED Indicator** – inconspicuous LED light level indicator for locating in a dark room
- **3-way switching applications** – pair with Lumina Gateway for an energy management solution
- **Standard size for seamless installation** – the DL1KDv fits in a standard single-gang wall box
- **Complies with IEEE 802.15.4 standards** – for domestic and international wireless networks

## Leviton Manufacturing Co., Inc. Global Headquarters

201 N. Service Rd. Melville, NY 11747-3138 Tech Line: 1-800-824-3005 Fax: 1-800-832-9538


## Leviton Manufacturing Co., Inc. Energy Management, Controls and Automation.

4330 Michoud Blvd., New Orleans, LA, 70129 Tel: 1-504-736-9810 Fax: 1-504-253-2954

Visit our Website at: [www.leviton.com/emca](http://www.leviton.com/emca)

©2016 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

**WIRING DIAGRAM**




Insulating label:  
 This wire is used in 3-way installations only.  
 For single pole installations, do not remove insulating label.

**SPECIFICATIONS**

Communication Frequency: 2.4GHz
Range: Up to 75' between Lumina RF devices
Load Ratings: 120V 1000W INC, 450W LED/CFL, 1000W FL Mark X, 1000VA MLV, neutral required

Lumina RF Full Phase 1000W Dimmer



**ORDERING INFORMATION**

DESCRIPTION	CAT. NO.
Lumina RF Full Phase 1000W Dimmer	DL1KD-1BZ

**Leviton Manufacturing Co., Inc. Global Headquarters**  
 201 N. Service Rd. Melville, NY 11747-3138 Tech Line: 1-800-824-3005 Fax: 1-800-832-9538

**Leviton Manufacturing Co., Inc. Energy Management, Controls and Automation.**  
 4330 Michoud Blvd., New Orleans, LA, 70129 Tel: 1-504-736-9810 Fax: 1-504-253-2954

Visit our Website at: [www.leviton.com/emca](http://www.leviton.com/emca)  
 ©2016 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

SAT-10099  
 REV SEP 2016