

Getting Started Guide



EB VERSION





See the complete line of Zigbee enabled dimmers, switches and plug-ins leviton.com/decorasmart





The Decora Smart™ Plug-in Outlet with Zigbee® technology is designed for use with Zigbee hubs. Using mesh networking technology Zigbee provides quick, reliable, secure communication to a wide variety of smart products.

Manual on/off control is convenient using the backlit, forward facing button. Add your outlet to a Zigbee hub to control it with your smartphone or voice interface





CALL

1-800-824-3005 (USA) 1-800-405-5320 (Canada)



ONLINE

leviton com/decorasmart



CHAT

leviton.com



dssupport@leviton.com

Your plug-in outlet works with:

Your Decora Smart plug-in outlet with Zigbee technology is compatible with a wide variety of load types. Consult the chart below to confirm compatibility.



RATINGS	
LED / CFL	600W - 120VAC, 60Hz
Resistive	1800W - 120VAC, 60Hz
Incandescent/Halogen	1800W - 120VAC, 60Hz
Fluorescent	1800VA - 120VAC, 60Hz
Inductive	1800W - 120VAC, 60Hz
Motor	1/2 HP, 9.8A
Operating Temp	0°C - 40°C (32°F - 104°F)
Operating Humidity	0-90% non-condensing
NETWORK	
Zigbee	Zigbee 3.0 Certified



Back-lit button -

- Shows on/off status of the load
- Helps locate the button in the dark
- Use to turn the load on/off
- Use to enter programming/joining mode




Load Connection

• Downward facing - great for use behind furniture



Something to consider:

Zigbee is a mesh network. It must be installed within 30 ft of hub or another Zigbee 3.0 compliant device.





- 1. Plug your appliance into the plug-in outlet.
- 2. Insert plug-in outlet into any non-switched 120VAC receptacle.
- Your plug-in outlet is now 3. ready to join the network.





To control your plug-in outlet with your phone, add it to a compatible Zigbee hub. Use the hub's app and follow the instructions for adding an outlet. When you power up your plug-in outlet it immediately enters inclusion mode (some hubs may use the term connect, join or pair).

If the hub uses older inclusion processes contact technical services for specific product instructions.



Manually start/stop joining

When you first power on your plug-in outlet or perform a factory reset the green status light will automatically flash. This indicates the plug-in is in joining mode. It will remain in this state for 30 minutes or until the plug-in is added to a network. To manually start or stop joining mode perform the following steps:

- Press and hold the button for 7 seconds. Status light will turn amber.
- **2a.** To start joining mode press the button 1 time. The status light will flash green rapidly to indicate it is in joining mode.
- 2b. To stop joining mode press the button 1 time. The plug-in will leave joining mode. NOTE: the device can still be operated manually even if not joined to a hub.



Factory default

To reset the outlet to factory settings and place in joining mode.

- 1. Hold the backlit button for a total of 14 seconds.
- 2. After the first 7 seconds the light turns amber. Continue to hold.
- After a total of 14 seconds, the light will quickly flash red/amber.
- 4. Release the button and the outlet will reset.



WARNING: TO AVOID FIRE, PERSONAL INJURY OR DEATH DO

NOT USE the outlet for the control of high power heating appliances such as portable heaters. There can be unexpected consequences if not used with care. For example, an empty coffee pot can be remotely turned on. If that should happen, your coffee pot could be damaged from overheating. If an electric heater is turned on by remote control while clothing is draped over it, a fire could result. This module will not control lighting that is used with electronic low-voltage and high frequency power supply transformers, nor high pressure discharge lamps (HID lighting). This includes mercuryvapor, sodium vapor and metal halide lamps.

WARNINGS:

- This product is to be installed and/or used in accordance with electrical codes and regulations.
- Indoor use only.
- If you are unsure about any part of these instructions, consult an electrician
- Unplug unit when servicing loads.
- Save this instruction sheet. It contains important technical data along Save this instruction sheet. It contains important technical data along with testing and troubleshooting information which will be useful after installation is complete.

Limited 5 Year Warranty

For Leviton's limited product warranty, go to **www.leviton.com**. For a printed copy of the warranty, call 1-800-824-3005.

FOR CANADA ONLY

For warranty information and/or product returns, residents of Canada should contact Leviton in writing at Leviton Manufacturing of Canada ULC to the attention of the Quality Assurance Department, 165 Hymus Blvd, Pointe-Claire (Quebec), Canada H9R 1E9 or by telephone at 1 800 405-5320.

FCC COMPLIANCE STATEMENT

The enclosed device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (i.) This device may not cause harmful interference (ii.) This device must accept any interference received, including interference that may cause undesired operation. Any changes or modifications not expressly approved by Leviton could void the user's authority to operate this equipment. This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to a rodio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- · Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- . Consult the dealer or an experienced radio/TV technician for help.

FCC CAUTION

Any changes or modifications not expressly approved by Leviton Manufacturing Co., Inc., could void the user's authority to operate the equipment.

FCC SUPPLIER'S DECLARATION OF CONFORMITY:

Model DG15A - plug-in outlet is manufactured by Leviton Manufacturing Co., Inc., www.leviton.com.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

IC STATEMENT

This device complies with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

RF EXPOSURE AND CO-LOCATION:

To comply with FCC OET Bulletin 65 and ISED RF exposure limits for general population and uncontrolled exposure, this device shall be installed and operated with a minimum distance of 7.9 inches (20 cm) between the radiator and your body. Also, must not be co-located or operated in conjunction with any other antenna or transmitter.

Copyright and Trademark Information

The Leviton logo and Decora Smart are trademarks of Leviton Manufacturing Co., Inc. Zigbee is a U.S. registered trademark of Zigbee Alliance. Use herein of other third party trademarks, service marks, trade names, brand names and/or product names are for informational purposes only, are/may be the trademarks of their respective owners; such use is not meant to imply affiliation, sponsorship, or endorsement. No part of this document may be reproduced, transmitted or transcribed without the express written permission of Leviton Manufacturing Co. Inc.

Copyright 2020 Leviton Mfg. Co., Inc.

WEB VERSION

If you need help...

- CALL 1-800-824-3005 (USA) 1-800-405-5320 (Canada)
- **ONLINE**leviton.com/decorasmart
- CHAT leviton.com
- EMAIL dssupport@leviton.com

Leviton Manufacturing Co., Inc. 201 North Service Road, Melville, NY 11747 Telephone: 1-800-824-3005

Visit Leviton's website at www.leviton.com © 2020 Leviton Manufacturing Co., Inc. All rights reserved.

Specifications subject to change at any time without notice.