


8 Port PoE Switch

Connected Home



APPLICATION

The POENS-8PT combines a small, high efficiency 8-Port 10/100Mbps Ethernet switch with IEEE 802.3af Power over Ethernet (PoE) capability on all 8 ports. It can be used to provide power to up to 7 Leviton OmniTouch 7 touchscreens (one port must be connected to the network).

When connecting an OmniTouch 7 touchscreen to the network, a UTP Cat-5/5e (4-pair) cable is required for operation. Run the cable between the location of the POENS-8PT and the location of the OmniTouch 7 touchscreen.

The POENS-8PT is a Power Source Equipment (PSE) device that is fully compatible with Powered Devices (PD) that comply with the IEEE 802.3af standard. The PoE ports on the POENS-8PT can also be used to power other Powered Devices (PD), such as the Leviton BitWise BC4, Leviton Intercom Door Station, OT7 Leviton PoE IP cameras, PoE Wireless Access Points, PoE Printers, etc.) without requiring additional power on the network. Each of the PoE ports can provide 15.4 Watts of power as well as 10/100M data transmission through the traditional UTP cable to the Powered Device.

The POENS-8PT is supplied with an external 48VDC power adaptor. No configuration is required and installation is quick and easy. Support for automatic MDI / MDI-X on all of the ports eliminates the need for a crossover connection to another switch or hub. Auto-negotiation on each port senses the link speed (100 Mbps or 10 Mbps) of a network device and intelligently adjusts for compatibility and optimal performance.

WARRANTY INFORMATION

Two-Year Limited Warranty

Leviton Manufacturing Co., Inc. Global Headquarters

201 N. Service Rd. Melville, NY 11747-3138 Tech Line: 1-800-824-3005 Fax: 1-800-832-9538

Leviton Manufacturing Co., Inc. Energy Management, Controls and Automation.

4330 Michoud Blvd., New Orleans, LA, 70129 Tel: 1-504-736-9810 Fax: 1-504-253-2954

Visit our Website at: www.leviton.com/emca

©2016 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

SPECIFICATIONS

STANDARDS	IEEE 802.3 10BASE-T Ethernet, IEEE 802.3u 100BASE-TX Fast Ethernet, IEEE 802.3x Full Duplex Flow Control, IEEE 802.3af Power over Ethernet
PROTOCOL	CSMA/CD
DATA TRANSFER RATE	Ethernet: 10Mbps (half-duplex), 20Mbps (full-duplex) Fast Ethernet: 100Mbps (half-duplex), 200Mbps (full-duplex)
NETWORK CABLES	10BASE-T: 2-pair UTP Cat 3, 4, 5 up to 100 meters. 100BASE-Tx: 2-pair UTP Cat 5, 5e up to 100 meters.
NUMBER OF PORTS	8 x 10/100Mbps RJ-45 ports with 8 PoE enabled ports
AC POWER ADAPTOR	Input: 100VAC - 240VAC, 50Hz - 60Hz Output: 48VDC, 2.5A
POWER CONSUMPTION	6.4 watts, maximum (with no Powered Devices connected) 112 watts (8 PoE ports fully loaded)
TEMPERATURE/HUMIDITY	Operation: 32 °F - 104 °F; Storage: 14 °F - 158 °F Relative Humidity: 5% - 95%
DIMENSIONS	16cm W x 9.4cm D x 2.1cm H

ORDERING INFORMATION

DESCRIPTION	CAT. NO.
8-Port PoE Network Switch	POENS-8PT
PoE Switch Mounting Kit	POEMP-KIT

8 Port PoE Switch

Leviton Manufacturing Co., Inc. Global Headquarters

201 N. Service Rd. Melville, NY 11747-3138 Tech Line: 1-800-824-3005 Fax: 1-800-832-9538

Leviton Manufacturing Co., Inc. Energy Management, Controls and Automation.

4330 Michoud Blvd., New Orleans, LA, 70129 Tel: 1-504-736-9810 Fax: 1-504-253-2954

Visit our Website at: www.leviton.com/emca

©2016 Leviton Manufacturing Co., Inc. All rights reserved. Subject to change without notice.

SAT-10047